

2019-2020



DISPLAY COUNTERS

Refrigerated Display Counters - Table Top Display Counters

TEFCOLD refrigerated display counters are fantastic for storing and displaying food products in delis, bakeries, gas stations, corner shops or cafés.

The LPD and LCT ranges are high-quality products, designed to optimise running costs and provide the perfect display.

The LPD range is a top-class counter with key features such as double-glazed glass, anti-mist front, LED lights under every shelf and white glass shelves. They are all available with curved or flat glass fronts

LCT is a range of small countertop models, similar to the LPD range, also available with curved or flat glass fronts. However, they have chromed wire shelves and stainless steel finish.

UPD is a range of vertical refrigerated displays, also available in tall floor and countertop versions. They have the same features as the LPD and LCT models, but in a different, vertical design.



TEFCOLD LPD 900C-P/BLACK

Display counter in stainless steel with ventilated cooling.

The sliding doors gives easy access to the great displayed content.





Display Counters - Curved



LPD1500C-P/BLACK

- Stainless steel and gloss black glass frame
- · LED light under each shelf
- Adjustable shelves (one step)
- Double glazed glass / front anti mist
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet and castors
- Curved glass top / front







Sliding doors



LPD1200C-P/BLACK

Refrigerated Display Counters

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Double glazed glass / front anti mist
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet and castors
- Curved glass top / front



LPD 900C-P/BLACK

Refrigerated Display Counters

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Double glazed glass / front anti mist
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet and castors
- Curved glass top / front

MODEL		LPD 900C-P/BLACK	LPD1200C-P/BLACK	LPD1500C-P/BLACK
Gross / Net Volume	ι	238 / 158	328 / 218	480 / 244
Gross / Net Weight	kg	235 / 204	309 / 269	315 / 275
Climate Class		3	3	3
Temperature Range	°C	2 to 8	2 to 8	2 to 8
Door Number & Type		2 sliding glass doors	2 sliding glass doors	2 sliding glass doors
Shelves Number & Type		4 glass shelves	4 glass shelves	4 glass shelves
Interior Light		LED	LED	LED
Feet / Legs		4 adjustable feet	4 adjustable feet	4 adjustable feet
Castors		4 castors	4 castors	4 castors
Exterior Finish		Stainless steel / Glass	Stainless steel / Glass	Stainless steel / Glass
Interior Finish		Stainless steel / Glass	Stainless steel / Glass	Stainless steel / Glass
Thermometer		Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic
Noise Level	db(A)	48	48	48
Type of Cooling		Ventilated	Ventilated	Ventilated
Type of Defrost		Automatic	Automatic	Automatic
Refrigerant		R290	R290	R290
Refrigerant Charge	g	110	130	140
Input Power	W	598	580	798
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	5,3	7,07	8,2
Internal Dimension (WxDxH)	mm	840 x 510 x 820	1140 x 510 x 820	1440 x 510 x 820
External Dimension (WxDxH)	mm	905 x 750 x 1360	1205 x 750 x 1360	1505 x 750 x 1360
Packed Dimension (WxDxH)	mm	960 x 800 x 1480	1260 x 800 x 1480	1560 x 800 x 1480
40ft Container Load	pcs	28	23	15

DISPLAY COUNTERS I 103





Display Counters - Flat



LPD1500F-P/BLACK

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Double glazed glass / front anti mist
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet and castors
- Curved glass top / front







Sliding doors



LPD1200F-P/BLACK

Refrigerated Display Counters

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Double glazed glass / front anti mist
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet and castors
- Curved glass top / front



LPD 900F-P/BLACK

Refrigerated Display Counters

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Double glazed glass / front anti mist
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet and castors
- Curved glass top / front

MODEL		LPD 900F-P/BLACK	LPD1200F-P/BLACK	LPD1500F-P/BLACK
Gross / Net Volume	ι	275 / 140	377 / 191	480 / 244
Gross / Net Weight	kg	232 / 201	273 / 232	310 / 262
Climate Class		3	3	3
Temperature Range	°C	2 to 8	2 to 8	2 to 8
Door Number & Type		2 sliding glass doors	2 sliding glass doors	2 sliding glass doors
Shelves Number & Type		3 glass shelves	3 glass shelves	3 glass shelves
Interior Light		LED	LED	LED
Feet / Legs		4 adjustable feet	4 adjustable feet	4 adjustable feet
Castors		4 castors	4 castors	4 castors
Exterior Finish		Stainless steel / Glass	Stainless steel / Glass	Stainless steel / Glass
Interior Finish		Stainless steel / Glass	Stainless steel / Glass	Stainless steel / Glass
Thermometer		Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic
Noise Level	db(A)	48	48	48
Type of Cooling		Ventilated	Ventilated	Ventilated
Type of Defrost		Automatic	Automatic	Automatic
Refrigerant		R290	R290	R290
Refrigerant Charge	g	110	130	140
Input Power	W	480	580	685
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	5,77	7,21	8,37
Internal Dimension (WxDxH)	mm	840 x 510 x 670	1140 x 510 x 670	1440 x 510 x 670
External Dimension (WxDxH)	mm	905 x 745 x 1209	1205 x 745 x 1209	1505 x 745 x 1209
Packed Dimension (WxDxH)	mm	960 x 800 x 1320	1260 x 800 x 1320	1560 x 800 x 1320
40ft Container Load	pcs	56	46	30

DISPLAY COUNTERS I 105





Display Counters - Table Top



LCT900C-P

- Stainless steel
- LED interior light
- Double glazed glass
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet
- Curved glass top / front







Sliding doors



LCT750C-P

Refrigerated Display Counters

- Stainless steel
- LED interior light
- Double glazed glass
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet
- Curved glass top / front

DID YOU KNOW?

We offer refrigerated display counters with both curved and flat glass front.

Available as floor models and tabletop models.

MODEL		LCT750C-P	LCT900C-P
Gross / Net Volume	l	100 / 60	130 / 78
Gross / Net Weight	kg	87 / 63	94 / 70
Climate Class		3	3
Temperature Range	°C	2 to 8	2 to 8
Door Number & Type		2 sliding glass doors	2 sliding glass doors
Shelves Number & Type		2 wire shelves chrome	2 wire shelves chrome
Interior Light		LED	LED
Feet / Legs		4 adjustable feet	4 adjustable feet
Exterior Finish		Stainless steel / Glass	Stainless steel / Glass
Interior Finish		Stainless steel / Glass	Stainless steel / Glass
Thermometer		Yes	Yes
Type of Controller		Electronic	Electronic
Noise Level	db(A)	48	48
Type of Cooling		Ventilated	Ventilated
Type of Defrost		Automatic	Automatic
Refrigerant		R290	R290
Refrigerant Charge	g	45	45
Input Power	W	242	242
Voltage / Frequency	V/Hz	220-240/50	220-240/50
Energy Consumption	kWh/24h	3,8	4,5
Internal Dimension (WxDxH)	mm	640 x 450 x 400	840 x 450 x 400
External Dimension (WxDxH)	mm	700 x 560 x 670	900 x 560 x 670
Packed Dimension (WxDxH)	mm	784 x 641 x 790	984 x 641 x 790
40ft Container Load	pcs	153	126

107





Display Counters - Table Top



LCT900F-P

- Stainless steel
- LED interior light
- Double glazed glass
- Rear glass sliding doors
- Ventilated cooling
- · Adjustable feet
- Flat glass top







Sliding doors





- Stainless steel
- LED interior light
- Double glazed glass
- Rear glass sliding doors
- Ventilated cooling
- Adjustable feet
- Flat glass top

MODEL		LCT750F-P	LCT900F-P
Gross / Net Volume	l	120 / 67	160 / 88
Gross / Net Weight	kg	89 / 65	99 / 75
Climate Class		3	3
Temperature Range	°C	2 to 8	2 to 8
Door Number & Type		2 sliding glass doors	2 sliding glass doors
Shelves Number & Type		2 wire shelves chrome	2 wire shelves chrome
Interior Light		LED	LED
Feet / Legs		4 adjustable feet	4 adjustable feet
Exterior Finish		Stainless steel / Glass	Stainless steel / Glass
Interior Finish		Stainless steel / Glass	Stainless steel / Glass
Thermometer		Yes	Yes
Type of Controller		Electronic	Electronic
Noise Level	db(A)	48	48
Type of Cooling		Ventilated	Ventilated
Type of Defrost		Automatic	Automatic
Refrigerant		R290	R290
Refrigerant Charge	g	45	45
Input Power	W	242	242
Voltage / Frequency	V/Hz	220-240/50	220-240/50
Energy Consumption	kWh/24h	3,8	4,5
Internal Dimension (WxDxH)	mm	640 x 450 x 400	840 x 450 x 400
External Dimension (WxDxH)	mm	700 x 560 x 670	900 x 560 x 670
Packed Dimension (WxDxH)	mm	784 x 641 x 790	984 x 641 x 790
40ft Container Load	pcs	153	126





Display Counters



UPD200-I

- Double glass on four sides
- Adjustable wire shelves
- Glass door
- Internal LED light
- Aluminium finish
- Ventilated cooling
- Strong wheels for mobility



Adjustable shelves



Castors with and without brake



UPD60-I-BLACK

Refrigerated Display Counters

- Double glass on four sides
- Adjustable wire shelves
- Glass door
- Internal LED light
- Black finish
- Ventilated cooling
- Adjustable feet



UPD80-I-GREY

Refrigerated Display Counters

- Double glass on four sides
- Adjustable wire shelves
- Glass door
- Internal LED light
- Grey finish
- Ventilated cooling
- Adjustable feet

MODEL		UPD200-I	UPD60-I-BLACK	UPD60-I-GREY	UPD80-I-BLACK	UPD80-I-GREY
Gross / Net Volume	l	468 / 425	60 / 58	60 / 58	80 / 78	80 / 78
Gross / Net Weight	kg	200 / 185	32 / 30	32 / 30	39 / 36	39 / 36
Climate Class	,	4	4	4	4	4
Temperature Range	°C	2 to 12	2 to 12	2 to 12	2 to 12	2 to 12
Door Number & Type		1 hinged glass door	1 hinged glass door	1 hinged glass door	1 hinged glass door	1 hinged glass door
Shelves Number & Type		5 wire shelves white	2 wire shelves grey	2 wire shelves grey	3 wire shelves grey	3 wire shelves grey
Interior Light		LED	LED	LED	LED	LED
Feet / Legs		-	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Castors		4 wheels, 2 with brake	=	-	-	-
Exterior Finish		Aluminium / SS304	Black finish, ABS	Grey finish, ABS	Black finish, ABS	Grey finish, ABS
Interior Finish		Aluminium / SS304	Black finish, ABS	Grey finish, ABS	Black finish, ABS	Grey finish, ABS
Thermometer		Yes	Yes	Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic	Electronic	Electronic
Noise Level	db(A)	46	42	42	42	42
Type of Cooling		Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost		Automatic	Automatic	Automatic	Automatic	Automatic
Refrigerant		R600a	R600a	R600a	R600a	R600a
Refrigerant Charge	g	60	38	38	40	40
Input Power	W	315	164	164	184	184
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	7,3	1,9	1,9	1,9	1,9
Internal Dimension (WxDxH)	mm	638 x 638 x 1180	400 x 346 x 460	400 x 346 x 460	400 x 346 x 610	400 x 346 x 610
External Dimension (WxDxH)	mm	706 x 706 x 1800	428 x 386 x 855	428 x 386 x 855	428 x 386 x 1000	428 x 386 x 1000
Packed Dimension (WxDxH)	mm	760 x 820 x 1930	500 x 450 x 895	500 x 450 x 895	500 x 450 x 1045	500 x 450 x 1045
40ft Container Load	pcs	42	230	230	230	230

DISPLAY COUNTERS I